


OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER



TABLE OF CONTENTS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER



Introduction	2	Remote Transmitter Operation	10-11
Product Features	3	Front Panel Functions	12-13
Package Contents	4	Rear Panel Signal Connections	14-15
Initial Inspection	5	Rear Panel Signal & Power Connections	16-17
Maintenance & Cleaning	6-7	Specifications	18
Protection Systems	7	Dimensions	19
Installation, Use & Care	8-9	Optional Adjustments	20-25

INTRODUCTION

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER

Welcome to the Jeff Rowland Design Group “family” and congratulations on your purchase of what is unquestionably one of the world’s finest integrated amplifiers. With its combination of features such as numerous function control and interconnect possibilities, system configuration flexibility, precision electronic circuitry, exceptional efficiency, and accurately machined chassis components throughout, your CONCERTO Integrated Amplifier will offer you many years of musically satisfying enjoyment.

Please take a few minutes to read the remainder of this Owner’s Manual before proceeding with the installation of the

CONCERTO Integrated Amplifier. A thorough understanding of the operational features will allow you to gain the maximum performance and ease of use for which this amplifier was designed. Please note that your CONCERTO Integrated Amplifier serial number begins with the letters “PA.” This serial number is located on the rear panel of the chassis. Please include this number with any correspondence regarding your CONCERTO Integrated Amplifier. It has been my joy to create an audio component of enduring value that reflects the highest ideals of musical and artistic expression. It is my hope that these qualities will enrich your experience and pride of ownership.

If you have any additional questions regarding the installation or operation of the CONCERTO Integrated Amplifier, please contact your authorized Jeff Rowland Design Group dealer or check the Jeff Rowland Design Group web site at www.jeffrowland.com.


Enjoy the music!



Jeff Rowland
President,
Jeff Rowland Design Group

PRODUCT FEATURES

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER



- High efficiency ICEpower® power conversion technology generates high output power with very little heat.
- Two pairs XLR input connectors for balanced system configurations.
- Three pairs RCA input connectors for unbalanced system configurations.
- Two pairs of parallel, high-current, balanced line level preamplifier outputs to allow driving of external amplifiers, subwoofers, zones, etc.
- Fully-balanced transformer coupled inputs provide universal compatibility with other components and eliminate ground loop noise and EMI.
- Fully-balanced circuit topology implemented on all inputs and outputs.
- Bypass function allows for transparent use in combination audio/home theater systems.
- Low noise, high-current, switch-mode power supply provides highest performance under all operating and AC line conditions.
- CE approved speaker output terminals require no tools for secure, low resistance connections.
- Low power consumption permits constant power-up operation to eliminate warm-up time.
- Full electronic and thermal protection modes guard against output overloads and short circuits.
- Optical encoder type volume control maintains quiet, trouble free performance and accuracy over the entire lifetime of the product.
- Dual range volume control allows large volume level changes when knob is rotated abruptly, yet allows small, precise volume level changes when knob is rotated slowly.
- Six function, hand-held infrared remote control.
- Ultra-low resonance, structurally rigid chassis, precision-machined from a solid block of aircraft grade 6061-T6 aluminum.
- Optional plug-in phono cards (installed internally) convert Line Input 2 to high performance phono inputs. Three gain and loading options can accommodate moving magnet (MM), moving coil (MC) cartridge types and high output moving coil cartridge types.
- Speaker outputs are fully balanced to provide maximum immunity from RF contamination due to high output common mode noise rejection.

PACKAGE CONTENTS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER


Ensure that all of the auxiliary components listed below are enclosed within the shipping carton and accessory box. Refer to the illustrations and verify that the proper components are included.




CONCERTO INTEGRATED AMPLIFIER




REMOTE TRANSMITTER



OWNER'S MANUAL



AC POWER CABLE



WARRANTY CARD

INITIAL INSPECTION

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER



Inspect the shipping container for damage. If any portion of the shipping container, packing material, amplifier, or accessories are damaged or missing, notify your dealer and the shipper (if a claim is to be made) immediately.

NOTE: Many shippers require notification and inspection within 24 hours of delivery to determine the nature of damages incurred.

Your CONCERTO Integrated Amplifier has undergone extensive performance evaluations, listening tests, quality control inspections, and a minimum 72 hour burn-in period prior to shipment and should therefore be in perfect operating condition upon delivery. If the amplifier does not operate correctly, please notify your dealer immediately.

We strongly suggest that you save all of the packing materials. If the amplifier is returned to your dealer or JRDG, the original packing materials must be used for shipment to avoid possible damage. Neither JRDG nor the shipper can be held responsible for damages incurred during transit if the original factory packing is not used. All factory returns require that JRDG issue a Return Authorization (RA) number prior to shipment.

MAINTENANCE & CLEANING

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER


All JRDG products are designed to provide a lifetime of enjoyment and listening pleasure. The CONCERTO Stereo Amplifier is uniquely constructed from a solid block of precision-machined aluminum. It's chassis is sealed to prevent dust from entering the interior of the chassis and thus should never need interior cleaning during the lifetime of the product. All internal circuitry is maintenance-free such that no adjustments of any kind are necessary over the lifetime of the product. If the amplifier is ever in need of service, updating, or upgrading, it should only be returned to an authorized repair facility or technician for servicing.

The front panel of the unit is precision-machined in a unique process that incorporates a diamond tipped cutting tool. This process was refined over many years to produce an attractive and unique appearance. Because the surface is not finished in the typical fashion of most audio and video equipment, there are a few rules that must be kept in mind when cleaning the equipment.

- Please allow the front panel, which is coated with an automotive-grade polyurethane finish, to cure for 6 months before attempting to clean it. This will prevent small scratches from marring the surface before the surface coating has had a chance to harden completely.
- The front panel of the unit should never be cleaned with anything other than a very soft cotton cloth and plain water or fine oil-based furniture polish. Because of the fine finish of the front panel, use of any other cleaning agent may permanently scratch the finish.
- The top cover, sides and bottom are protected by a durable black anodized finish and can be cleaned with a soft cotton cloth (such as an optical lens cleaning cloth or fine furniture polishing rag) dampened with plain water. Water should be applied directly to the cloth and not the chassis. A very mild plastic or glass cleaner that does not contain ammonia may also be used. If a mark has been left on the chassis, do not use any type of abrasive or chemical cleaner to remove the mark.

If you have any questions about the care or cleaning of your CONCERTO Integrated Amplifier, please contact your dealer or the JRDG factory before attempting to clean the chassis. The use of a cleanser or abrasive to clean the chassis that has not been approved by the factory will almost certainly damage the finish and will not be covered under warranty.

NOTE: Cleaner/polish should be applied directly to the cloth and not the chassis.



PROTECTION SYSTEMS

The CONCERTO Integrated Amplifier is equipped with internal fuses for protection against excessive AC current draw; however, since no protection circuitry or system can completely protect a product from every electrical hazard, certain precautions should be observed. In the event of severe voltage hazards such as lightning or when the amplifier will not be used for extended periods of time, the amplifier should be unplugged from the AC mains to avoid potential damage to the internal circuitry. All other audio/video system components should also be disconnected from AC mains power as hazardous voltages can easily travel throughout an interconnected system.

INSTALLATION, USE & CARE

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER

Locate the amplifier as close as possible to its final installation point. Allow access to the rear panel for making connections. Due to its design, the CONCERTO Integrated Amplifier is energy efficient, eliminating the need for heatsinks or forced-air cooling. As a result, the CONCERTO Integrated Amplifier can be housed in a cabinet or custom enclosure with no fear of overheating.

The efficient and compact design of the CONCERTO allows it to be installed in any number of music, film and surround sound systems. For connection instructions for a typical two-channel stereo system, please see page 15 of this manual. For instructions regarding the use of the BYPASS INPUTS for surround sound or home theater system use, please see page 15 of this manual.

The main chassis of the CONCERTO is precision-machined out of a solid block of aluminum to create as rigid an enclosure as possible, impervious to lateral and torsional forces. The amplifier is particularly non-resonant; however, various damping and resonance control accessories may be used to yield greater audio performance in some audio systems.

RISK OF ELECTRICAL SHOCK!



WARNING: Do not attempt to access the interior of the CONCERTO INTEGRATED AMPLIFIER by removing the bottom cover. Doing so will void your warranty and could expose you to dangerous, potentially lethal electrical voltages.

The JRDG CONCERTO Integrated Amplifier has been designed to operate at the highest level of efficiency and performance in any normal operating situation; however, there are a few important use and care principles that must be kept in mind when operating the amplifier:

- Do not expose the amplifier to rain, moisture, or excessively damp conditions.
- Make sure that the voltage indicated on the rear panel matches the mains voltage in your area.
- The CONCERTO Integrated Amplifier must not be modified in any way, other than according to official service bulletins from JRDG. Otherwise, the factory warranty will be immediately voided.
- Be sure the amplifier is turned off or unplugged from the AC mains supply before connecting or disconnecting any loudspeaker or interconnect cables.
- When operating the CONCERTO, a properly grounded AC receptacle should be used. A potential shock hazard may result if the supplied 3-wire, grounded AC cable ground terminal is defeated or lifted or the unit is connected to a 2-wire ungrounded AC outlet.
- The CONCERTO is designed to perform optimally with no adjustments or maintenance for the lifetime of the product. Do not attempt to open the bottom cover of the amplifier and refer all service issues to qualified personnel. The voltages inside the CONCERTO can be hazardous.
- Because of the energy efficiency of the CONCERTO, there is no need to unplug the unit or turn the unit off when not in use except in the event of severe voltage hazards as mentioned previously.

REMOTE TRANSMITTER OPERATION

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER

The CONCERTO Integrated Amplifier is equipped with a wireless, infrared (IR) remote transmitter, allowing convenient wireless control of the most commonly used functions from the listening position. An explanation of these functions and battery installation follows.


NOTE: Placing the amplifier in extremely high ambient light conditions may cause erratic remote control operation. The IR sensor, located within the volume level display, must not be exposed to direct sunlight or spotlights.

(1) INPUT SELECT: This button will select the desired input, the input number corresponding to the numbering of the inputs on the rear panel. Each press of this button will scroll to the next successive input. Once Input 5 has been reached, the next press of the INPUT button will select the BYPASS input. Another press of the INPUT button will return the selection to Input 1.

(2) MUTE: This button will immediately mute the outputs of the amplifier. The volume display will continue to show the present location of the volume control. Pressing this button a second time will reactivate the outputs of the amplifier.

(3) VOLUME ▲: The VOLUME UP button will increase the output level of the amplifier in 0.5 dB increments. Holding this button down will cause the volume level to continuously increase until the button is released or until 99.5 is displayed on the volume display.

(4) VOLUME ▼: The VOLUME DOWN button will decrease the output level of the amplifier in 0.5 dB increments. Holding this button down will cause the volume level to continuously decrease until the button is released or until 00.0 is displayed on the volume display.




(5) BAL L: This button will shift the output of the amplifier towards the left channel. Each press of the button will increase the output of left channel by 0.5 dB and decrease the level of the right channel by 0.5 dB. A total shift of 6 dB is possible. The balance control is not continuous; holding the button down will not continue to shift the balance. The button must be repeatedly pressed to continue to activate the balance shift towards the left channel.

(6) BAL R: This button will shift the output of the amplifier towards the right channel. Each press of the button will increase the output of right channel by 0.5 dB and decrease the level of the left channel by 0.5 dB. A total shift of 6 dB is possible. The balance control is not continuous; holding the button down will not continue to shift the balance. The button must be repeatedly pressed to continue to activate the balance shift towards the right channel.

NOTE: To return the balance to the center or 0 dB position, press and hold the MUTE button on the front panel of the preamplifier for 3 seconds. This will reset all microprocessor controlled functions and return the balance position to L/R +/-0 dB.

(7) BATTERY REPLACEMENT: When the remote begins to become weak or will not function, it is likely necessary to replace the battery. Access to the battery is gained by removing the two Phillips head screws that secure the back cover of the remote transmitter unit. The old battery can be removed from the snap-on BATTERY TERMINAL and a new battery reinstalled. A standard alkaline battery is recommended.

NOTE: When removing the old battery, wait at least 30 minutes before installing a new battery to allow the internal circuitry to discharge completely and reset.




FRONT PANEL FUNCTIONS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER

Before attempting any system interconnection, please familiarize yourself with the front panel controls and indicators of the CONCERTO Integrated Amplifier. The descriptions refer to the illustration below.

(1) INPUT INDICATORS: Inputs 1 through 5 have a small indicator light above the Input Selector Buttons. An indicator will illuminate blue when selected to show that the input is currently active.

(2) INPUT SELECTOR BUTTONS: Pressing these buttons selects an input source (CD, tuner, phono, etc.) connected to the associated rear panel inputs (see Rear Panel Signal Connections on page 14). To select a desired input, press the corresponding Input Selector Button. When an input is activated, the small, blue Input Indicator above the Input Selector Button will illuminate.



(3) BYPASS MODE: The Bypass Mode allows the CONCERTO to be installed in a home theater or surround sound system for optimal playback of stereo music sources when the multi-channel system is not in use. Pressing this button will allow a multi-channel processor to bypass the amplifier functions of the CONCERTO, with the volume controlled only by the external processor. The indicator light above the BYPASS button will illuminate yellow to show that the Bypass function is active.

NOTE: Do not connect a source component to the BYPASS INPUTS if it does not have its own volume control. The volume control of the CONCERTO is inactive when Bypass Mode is selected.

(4) PHASE: Pressing this button will invert the phase of both channels of the selected input and illuminate the green indicator light above the PHASE button. Pressing this button again will turn off the light and return the phase to uninverted polarity.

(5) MUTE MODE: Pressing the MUTE button will mute the speaker and line outputs of the CONCERTO and illuminate the red indicator light above the MUTE button. Pressing this button again will turn off the light and restore the output of the amplifier to the previous volume setting.

(6) VOLUME DISPLAY: This display shows the current volume of the selected input numerically, from 00.0 to 99.5, in 0.5 dB increments. If desired, the volume display can be configured to turn off 5 seconds after receiving any

command from the front panel or the Remote Transmitter. Please contact your dealer about this function. The volume display also contains the infrared (IR) receiver for receiving remote commands.

(7) VOLUME CONTROL: Rotation of the volume control knob clockwise will increase the output level of the CONCERTO. Rotation of the knob counter-clockwise will decrease the output level. The CONCERTO features a dual-range volume control system: rotating the volume knob slowly will cause the volume to increase or decrease in small, precise steps. Rotating the knob abruptly will result in large, immediate changes to the output level.

NOTE: When the volume control is set to 79.5, the preamplifier section is set for unity (0 dB) gain from any input to any preamplifier (preout A or B) output.

REAR PANEL SIGNAL CONNECTIONS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER

The CONCERTO Integrated Amplifier offers unprecedented compatibility with associated audio and A/V components. When connecting or disconnecting interconnect cables, the CONCERTO should be switched off or unplugged from the AC mains supply.

(1) UNBALANCED INPUTS: If you are using unbalanced RCA interconnects from your source components (CD player, tuner, etc.), they should be connected to unbalanced INPUTS 1 and 2. If you have had the optional phono section installed in the CONCERTO, the interconnects from the turntable should be installed into INPUT 2. For more information about the phono option, please contact your dealer.

NOTE: An RCA "shorting" plug must be installed into PHONO/INPUT 2 if phono cards are installed and your phono turntable is not connected. See phono card adjustments section.



(2) BALANCED INPUTS: If you are using balanced XLR interconnects from your source components, they should be connected to balanced INPUTS 4 and 5. A slight mechanical click may be heard when the balanced XLR interconnect cables are correctly installed and locked into the rear panel connector. The unlocking tab must be pressed to disconnect the XLR interconnect cable from the amplifier. The XLR inputs may be left open if unused. Any XLR input can be converted to RCA input by installing an XLR to RCA adapter, available from your JRDG dealer.

NOTE: Pin 2 of each XLR connector is signal positive with respect to each RCA input. Also, JRDG recommends balanced cables as the preferred method of interconnection.

(3) BYPASS INPUTS: If the CONCERTO is installed in a home theater or surround sound system, the Left Front and Right Front output connections from the surround processor should be installed in the BYPASS input connections. The CONCERTO will only accept balanced XLR interconnects from the surround processor. If an unbalanced connection is required, install an XLR to RCA adapter, available from your JRDG dealer.

(4) GROUND LUG THUMBSCREW: This connection is reserved for units with the optional phono section installed. When connecting a turntable, the ground or earth lead should be connected to the Ground Lug Thumbscrew to eliminate any ground noise in the system.

(5) BALANCED LINE OUTPUTS: The CONCERTO has two sets of balanced line-level outputs for auxiliary amplification, biamplification, powering of an active subwoofer, or for feeding audio to an amplifier in a separate room or zone. If your additional amplifiers accept only RCA unbalanced cables, it is recommended that the XLR balanced outputs are converted to RCA outputs with a balanced single-ended adaptor box (Model PC-2XR) available from Jensen Transformers, www.jensen-transformers.com.


NOTE: Both sets of line level outputs have equal output levels. Thus, if Preout B outputs are used to feed a separate room or zone, they cannot be controlled independently from the main room.

REAR PANEL SIGNAL & POWER CONNECTIONS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER

! WARNING: Both positive and negative outputs are electrically active with respect to chassis and/or system ground potential. Therefore, this amplifier cannot be used in certain loudspeaker switching configurations, such as those used in retail demonstrations. Failure to avoid these precautions may short the outputs to ground and can result in damage to the amplifier and will void the warranty. Certain subwoofer speakers which derive signals from amplifier outputs will require additional circuitry to properly isolate the amplifier output. Please contact JRDG before connecting these types of subwoofers.

(A) LOUDSPEAKER OUTPUTS: Unscrew the knob that secures the speaker output connectors on both the LEFT SPEAKER OUTPUT and the RIGHT SPEAKER OUTPUT and pull the securing block out far enough to allow access to the binding posts. Install the positive (usually red) loudspeaker cable spade terminal to the positive (+) binding post and the negative spade terminal to the negative (-) binding post on both the LEFT and RIGHT CHANNEL. Secure the loudspeaker connections by tightening the knob securely with your fingers. The CONCERTO will only accept spade terminated loudspeaker cables. Banana plugs or bare wire connections can be used but require an optional clamp available from your JRDG Dealer.



POWER CONDITIONING: AC power conditioners and AC mains power cables are a common accessory in many high performance audio and video systems and can be used to improve the quality of reproduction in certain instances. We have tried to provide the best possible basic power cord with the CONCERTO; however, many users may wish to use aftermarket AC power cords available from many cable manufacturers. Since we have not found an optimal universal power conditioner or cable we cannot recommend any particular type or brand for use with the CONCERTO. Please use your dealer's help and knowledge as a resource to select the proper accessories for your individual system needs.

NOTE: Due to the exceptionally low power consumption rating of the CONCERTO, it is recommended that the unit simply be left on when not in use. Also, the CONCERTO includes a user-accessible fuse (E) for added safety and protection. In the unlikely event that this fuse has blown, it must be replaced with an exact match. (230V, 6.3A, or 100/120V, 10A)



WARNING: Serious damage to internal circuitry can occur if improperly wired or unapproved AC power cords are used. Your dealer can be a helpful resource for selecting the proper accessories for your needs.




SPECIFICATIONS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER

Output Power, Continuous RMS	250 watts @ 8 ohms, 500 watts @ 4 ohms
Frequency Response	5 Hz – 70 kHz, -3 dB @ 8 ohms
Gain Structure	Preamp Section 20 dB, Amp Section 27 dB
Peak Output Current	35 amps
Dynamic Range	117 dBa
THD + Noise, 0.1 watts – 500 watts, 4 ohm	< .05%, typically .006% @ 1 kHz
Load Impedance Range	2 ohms – 16 ohms
Input Impedance	40k ohms Balanced or Unbalanced
CCIF Intermodulation Distortion, 19/20 kHz	< .002%
Damping Factor @ 1 kHz	> 1000
Common Mode Rejection Ratio	> 90 dB, 20 Hz – 20 kHz
Absolute Phase	Non-inverting, Pin 2 Positive
Inputs	2 pair Balanced (XLR) 1 pair Balanced Unity Gain (Bypass) 3 pair Unbalanced (RCA)
Outputs	2 pair Balanced (XLR) Line Level 1 pair CE-Approved Binding Posts
Power Consumption	Idle – 22 watts, Maximum – 1000 watts
Amplifier Weight	26 lbs. / 12.1 kg
Overall Amplifier Dimensions (H) x (W) x (D)	3.2" x 17.3" x 13.9" 80mm x 440mm x 353mm

DIMENSIONS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER



OPTIONAL ADJUSTMENTS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER

RISK OF ELECTRICAL SHOCK!

WARNING: The instructions in this section are meant for qualified JRDG service personnel only; however, if you as an end user choose to attempt these adjustments yourself, JRDG cannot be held liable for any damage that may occur to your CONCERTO Integrated Amplifier because of your actions. Further, accessing the interior of your CONCERTO by removing the bottom cover can expose you to dangerous, potentially lethal electrical voltages. Thus, JRDG cannot be held liable for any injury you may sustain should you undertake any of these adjustments yourself.

DISPLAY BLANKING ADJUSTMENTS

The display of the CONCERTO can be configured to turn off ("go blank") five seconds after each user command, whether from the front panel controls or from the remote control.

STEP 1: Unplug the CONCERTO power cable from the wall AC outlet.

STEP 2: Place the unit upside-down on a soft, clean surface. Using a #2 Phillips screwdriver, remove the twelve screws that secure the bottom cover of the unit.

STEP 3: Using a small flat-blade screwdriver, compress the spring clips on each side of the AC Receptacle while pushing the Receptacle outward. Push the Receptacle out as shown in FIGURE 1, to expose the jumpers below.




FIGURE 1: Partial Removal of AC receptacle is necessary to access the jumpers that are located underneath (See step 3 for instructions)




FIGURE 2: Location of jumpers on back of the rear panel




FIGURE 3: Display blanking settings

STEP 4: Locate jumper J17 on the rear panel board of the unit. Using needle-nose pliers, move the jumper from between pins 2 and 3 to pins 1 and 2, DISPLAY BLANKING ON. (See FIGURES 2 and 3)

STEP 5: Replace the bottom cover. Using a #2 Phillips screwdriver, reinstall the twelve screws that secure the bottom cover to the chassis.

OPTIONAL ADJUSTMENTS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER




FIGURE 4: Location of jumpers on back of the rear panel




FIGURE 5: Remote control frequency settings

REMOTE CONTROL FREQUENCY

A second remote control operational frequency may be selected for the CONCERTO if interference occurs when using the factory-default settings. This interference could occur either from the CONCERTO's remote interfering with other equipment or vice versa.

STEP 1: Unplug the CONCERTO power cable from the wall AC outlet.

STEP 2: Place the unit upside-down on a soft, clean surface. Using a #2 Phillips screwdriver, remove the twelve screws that secure the bottom cover of the unit.

STEP 3: Using a small flat-blade screwdriver, compress the spring chips on each side of the AC Receptacle while pushing the Receptacle outward. Push the Receptacle out as shown in FIGURE 1, to expose the jumpers below.

STEP 4: Locate jumper J18 on the rear panel board of the unit. Using needle-nose pliers, move the jumper from between pins 2 and 3 to pins 1 and 2. (See FIGURES 4 & 5)

STEP 5: Replace the bottom cover. Using a #2 Phillips screwdriver, reinstall the twelve screws that secure the bottom cover to the chassis.

STEP 6: Using a #1 Phillips head screwdriver, remove the two screws that secure the remote transmitter housing. Open the housing.

STEP 7: Locate switch position SW7. Adjust slider #1 of the switch to the upper 'ON' position. This switch now corresponds with the new setting on jumper J18 of the rear panel board.

STEP 8: Test the remote with the CONCERTO Integrated Amplifier to make sure that the units operate properly together.

STEP 9: After verifying proper operation, replace the remote housing and reinstall the two screws that secure the housing.






FIGURE 6: Remote transmitter housing with details of switch position SW7



SWITCH SW7 POSITION 1 (DEFAULT)



SWITCH SW7 POSITION 2

FIGURE 7: Detail of switch position SW7

OPTIONAL ADJUSTMENTS

OWNER'S MANUAL CONCERTO INTEGRATED AMPLIFIER

PHONO CARD ADJUSTMENTS

If the Phono Card option has been factory installed, so that Input 2 on the rear of the CONCERTO is dedicated for phono operation only, the following adjustments can be made to optimize the performance of a particular phono cartridge. These adjustments include both cartridge loading and overall phono amplifier gain.

STEP 1: Unplug the CONCERTO Integrated Amplifier power cable from the wall AC outlet.

STEP 2: Place the unit upside-down on a soft, clean surface. Using a #2 Phillips screwdriver, remove the twelve screws that secure the bottom cover of the unit.

STEP 3: Carefully remove the phono card from the back panel by easing it gently back and forth until it separates from the unit. (See FIGURES 8 and 9)



FIGURE 8: Location of Phono Cards on the inside back panel



FIGURE 9: Phono Card removal

STEP 4: Locate the LOAD and GAIN switches on the phono card. (See FIGURE 10) Adjust the Load Resistance and Gain settings on the plug-in Phono Card as shown in the tables in FIGURES 11 and 12.

STEP 5: Replace the bottom cover. Using a #2 Phillips screwdriver, reinstall the twelve screws that secure the bottom cover.




FIGURE 10: Detail of Phono Card PCB default settings (LOAD-400 ohms, 1-OFF, 2-ON) (GAIN-62 dB, 1-OFF, 2-ON)

SWITCH POSITION	LOAD RESISTANCE (ohms)	PHONO CARTRIDGE TYPE
1: OFF 2: OFF	47K	MM OR HIGH OUTPUT MC
1: ON 2: OFF	100	MC ONLY
1: OFF 2: ON	400 (Default)	MM OR HIGH OUTPUT MC
1: ON 2: ON	85	MC ONLY

FIGURE 11: Table 1, Load Resistance Settings

SWITCH POSITION	GAIN (dB)	PHONO CARTRIDGE TYPE
1: OFF 2: OFF	44	MM ONLY
1: ON 2: OFF	55	SOME MM, HIGH OUTPUT MC
1: OFF 2: ON	62 (Default)	MC ONLY
1: ON 2: ON	64.5	MC ONLY

FIGURE 12: Table 2, Gain Settings



CAUTION: Do not select the 47K ohm Load Switch Position unless a turntable, phono cartridge or RCA “shorting” plug is connected to INPUT 2/PHONO! If a phono turntable or RCA “shorting” plug is not connected to INPUT 2/PHONO and the card is installed, set the Load Switch Position to any position except 47K. The 47K ohm Load Switch Position is used for Moving Magnet or High Output Moving Coil phono cartridges only!



JEFF ROWLAND
DESIGN GROUP